

**Approvals**



5A-300V  
not approved

**Electrical**

Rated voltage 450 V  
 Rated current 8 AMP  
 Contact resistance 20 mΩ  
 Insulation resistance 500 MΩ/DC 500 V  
 Withstanding voltage AC 2000 V/1 min  
 Wire range 1,5 mm<sup>2</sup> 22÷16 AWG

Torque ---  
 Temp. Range -40°C + 105°C  
 Stripping length 8 mm  
 Max sold. time +250°C for 5 sec.

**Dimensions**

Pitch 3.5 mm  
 Poles 1÷xx

**Material**

Housing PA66 UL94V0  
 Pin Phosphore bronze, Ni plated  
 Cage ---  
 Screws ---  
 Side Block ---  
 Nut screw ---  
 Clamp ---

**General description of ordering code**

Series	n. Poles	Pitch	Version	Color	Custom
MRM1	1÷xx	-3.5	-VP		

**Version Date**

17/01 25/10/17



**euro-block**



**UNITS:** mm

**SHEET SIZE:** ISO A4

**SCALE:** 3:1

> 0 ~ 3

> 3 ~ 18

> 18 ~ 50


> 50 ~ 120

± 0.12

± 0.15

± 0.3

± 0.5



First angle projection

**MRM1-3.5-VP**